vivitek®
Vivid Color. Vivid Life.

MULTIMEDIA
PROJECTOR | **D968U**

High Brightness WUXGA Multimedia Projector

The Vivitek D968U is a high brightness WUXGA multimedia digital projector. The D968U delivers a amazing image quality and would be perfectly suited for large meeting rooms thanks its 4800 ANSI Lumens of brightness and an outstanding contrast ratio of 10.000:1. The D968U offers also exceptional color saturation.

Features

- Native WUXGA (1920 x 1200) resolution

- High Brightness of 4800 ANSI lumens and high 10,000:1 Contrast ratio ensuring a crisp and sharp image

- 5 segment color wheel for exceptional color reproduction

- Assortment of connectivity options for easy connection to a variety of multimedia devices (HDMI, DisplayPort)

- New efficient lamp offering up to 4,000h life

- Top-loading, sliding cover for quick and easy lamp replacement

- Direct 3D through HDMI

- Network ready for integration and system administration via RJ45

- Built-in 5W loudspeaker

- Crestron® RoomView™ certified

- Security solutions include: Kensington® security slot, security bar, keypad lock

Specifications	
Brightness	4800 ANSI Lumen
Native Resolution	WUXGA (1920 x 1200)
Max. Resolution	WUXGA (1920 x 1200) @60Hz
Contrast Ratio	10,000:1
Lamp Life and Type	2,500/3,500/4,000h (Normal/Eco/Dynamic Eco Mode), 310W
Display Type	Single 0.67" DLP® Technology by Texas Instruments
Throw Ratio	1.6 -1.92:1 (Distance/Width)
Image Size (Diagonal)	24.3" to 300"
Projection Distance	1 – 10 m
Projection Lens	F=2.5, f=23.5-28.2mm
Zoom Ratio	1.2x
Aspect Ratio	16:10 Native, 4:3 & 16:9 Compatible
Offset (full image height)	115%
Keystone Correction	±40º Vertical (Autokeystone)
Speaker	5 W (SPL)
Projection Method	Table Top or Ceiling Mount (Front or Rear)
Video Compatibility	SDTV(480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L)
I/O Connection Ports	VGA-In (x2), HDMI v.1.4 (x2), Display Port, Composite Video, Audio-In (RCA), Audio-In, (Mini-Jack), VGA-Out (15pin D-Sub), AudioOut, (Mini-Jack), RJ45, 12v Trigger,RS-232, 3D-Sync Out, USB Service only
Security	Kensington® Lock Port
Weight	3.5 Kg
Dimensions (W x D x H)	333 x 255 x 113 mm
Noise Level	40dB/35dB (Normal/Eco Mode)
Power	Supply: AC 100-240V, 50/60Hz Consumption: 370W/300W (Normal/Eco Mode) <0.5W (Standby Mode)
Warranty	Standard: 3 year warranty on projector, 1 year or 1,000 hrs on lamp
Standard Accessories	AC Power Cord, VGA Cable, Carrying Case, Remote Control, Lens Cap, Documentation Kit
Optional Accessories	Replacement Lamp
UPC	814964 338969