

NovoTouch

LK8630i



| | |
|-----------------------------------|---|
| Model Name | NovoTouch LK8630i |
| Display Technology | Backlit LED (IPS Panel) |
| Panel Size; Aspect Ratio | 86", 16:9 |
| Brightness | 330cd/m2 |
| Contrast Ratio (Typical) | 1,200:1 |
| Native Resolution | 4K Ultra-HD (3840 x 2160) |
| Viewing Angle (Horiz/Vert) | 178°/178° |
| Refresh Rate (Hz) | 60Hz |
| Display Color (Bit) | 1.06 billion (10-bit) |
| Orientation | Landscape |
| Touch Technology | Infrared Touch |
| Touch Points | 10 Writing, 20 Touch |
| Surface Protection | 4mm Thick Toughened Glass (Level 7H on Mohs Scale of Mineral Hardness) |
| Minimum Touch Object | Single-Touch ≥Φ6mm and Multi-Touch ≥Φ8mm |
| Touch Tools | Finger, Stylus, Glove, Opaque Objects |
| Gestures Supported | Yes |
| System Version | Android™ v6.0 |
| CPU | RK3399, Dual-Core ARM® Cortex® A72 and Quad Core ARM® Cortex® A53 |
| GPU | Mali™ T860 |
| RAM | 4GB DDR3 |
| Internal Storage | 16GB |
| OS Compatibility | Windows® (Windows 7 and above: Driver Free), Mac® (10.10 and above), Android™ (2.2/2.3/4.0/4.1/4.2 (Kernel v3.5 and above - Driver Free), Chrome (v39 and above), Linux (Kernel v3.5 and above) |
| I/O Ports | HDMI v2 (x1), HDMI v1.4 (x2), DisplayPort (x1), VGA-In (x1), Audio-In (3.5mm) (x1), AV-In (x1), HDMI-Out (1080P) (x1), Audio-Out (3.5mm) (x1), Coaxial-Out (RCA) (x1), LAN (RJ45) (x1), RS232 (x1), USB Type A 2.0 (x4), USB Type A 3.0 (x2), USB Type B (x2) |
| Internal Speakers | 12W (x2) (Stereo) |
| Power Supply | AC 100-240V, 50/60Hz |
| Panel Dimensions | 1,988 x 1,178 x 99.6 mm |
| Panel Weight (Net) | 107 kg |
| What's included | Touch Screen Panel, NovoConnect Solution Module VKA05, Wall Mount WIB9060A, Documentation Kit, AC Power Cord, VGA Cable, USB Cable, Audio Cable, Stylus (x3), Remote Control with Batteries. |
| Options | NovoConnect Solution LauncherPlus QL300EU, NovoTouch Plug-In Windows OPS Module VKW21 |
| Model UPC Code | 813097023049 |
| Warranty | 3 years RTB |